




kg. 6,00



kg. 6,77



kg. 5,80



kg. 6,80

Tipo : Type :		B38/L		do: 38 mm	
Omologazione Homologation		PN	Coefficiente efflusso ridotto Low flow coefficient		Campo di taratura Setting range
CE - UKCA		40	0,76		0,3 - 30,0 bar
EAC		40	0,76		0,3 - 30,0 bar
ATEX Ex h II 2 Gb - UKEX		40	0,76		0,3 - 30,0 bar
ATEX Ex h II 2 Db - UKEX (1)		40	0,76		0,3 - 30,0 bar
ASME XIII - CRN (Canada)		40	0,629		1,0 - 30,0 bar
SELO - TSG		40	0,629		1,0 - 30,0 bar
CONFIGURAZIONE - CONFIGURATION					
Materiale Material		Ottone Brass	Mista Ottone-Acciaio inox Mixed Brass-Stainless steel		Acciaio inox Stainless steel
Modelli Model	Con ghiera With ring nut	Con ghiera With ring nut	Con ghiera With ring nut		
	Senza Ghiera Without ring nut	Senza Ghiera Without ring nut	Senza Ghiera Without ring nut		
	Con leva With lever	Con leva With lever	Con leva With lever		
	/	/	Con apertura pneumatica (2) Nith pneumatic opening		
	/	/	(2) Pneumatic with sensor		
Sedi di Tenuta Seal System	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICONE -60 / +200 °C PTFE -196 / +250 °C KALREZ -20 / +250 °C /	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICONE -60 / +200 °C PTFE -196 / +250 °C KALREZ -20 / +250 °C Metal -196 / +250 °C	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICONE -60 / +200 °C PTFE -196 / +250 °C KALREZ -20 / +275 °C Metal -196 / +450 °C		
	G.1"1/2 - 2" ISO228 R.1"1/2 - 2" EN10226 1"1/2 - 2" NPT / / / / / /	G.1"1/2 - 2" ISO228 R.1"1/2 - 2" EN10226 1"1/2 - 2" NPT 2" Tri Clamp DN40-50 DIN405-11851 DN40-50 PN16-40 2" 150-300 lb / /	G.1"1/2 - 2" ISO228 R.1"1/2 - 2" EN10226 1"1/2 - 2" NPT 2" Tri Clamp DN40-50 DIN405-11851 DN40-50 PN16-40 2" 150-300 lb / /		
Connessione Uscita Outlet Connection	G.2" ISO228 / / / / / /	G.2" ISO228 2" Tri Clamp DN50 DIN405-11851 DN50-65 PN16-40 2"-2"1/2-3" 150-300 lb / /	G.2" ISO228 2" Tri Clamp DN50 DIN405-11851 DN50-65 PN16-40 2"-2"1/2-3" 150-300 lb / /		
A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: INAIL (area ISPESL), TÜV, RINA, Bureau Veritas, ABS e Lloyd Register. On request tests can be made by the most prestigious societies, such as: INAIL (area ISPESL), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.					

Note: (1) No Modello Con leva / No Model With lever (2) Max 8 bar