



Tipo : Type :	C10	do: 10 mm
------------------	-----	-----------

Omologazione Homologation	PN	Coefficiente efflusso ridotto Low flow coefficient	Campo di taratura Setting range
CE - UKCA	25	0,69	0,3 - 16,0 bar
EAC	25	0,69	0,3 - 16,0 bar
ATEX Ex h II 2 Gb - UKEX	25	0,69	0,3 - 16,0 bar
ATEX Ex h II 2 Db - UKEX	/	/	/
ASME XIII - CRN (Canada)	25	0,712	1,0 - 16,0 bar
SELO - TSG	25	0,712	1,0 - 16,0 bar

CONFIGURAZIONE - CONFIGURATION			
Materiale Material	Ottone Brass	Mista Ottone-Acciaio inox Mixed Brass-Stainless steel	Acciaio inox Stainless steel
Modelli Model	Senza Ghiera Without ring nut	/	Senza Ghiera Without ring nut
	Con anellino With ring	/	Con anellino With ring
	/	/	/
	/	/	/
	/	/	/
	/	/	/
Sedi di Tenuta Seal System	N.B.R. (Std) -10 / + 100 °C	/	N.B.R. (Std) -10 / + 100 °C
	E.P.D.M. -50 / + 150 °C	/	E.P.D.M. -50 / + 150 °C
	VITON -20 / +200 °C	/	VITON -20 / +200 °C
	SILICONE -60 / +200 °C	/	SILICONE -60 / +200 °C
	PTFE -196 / +250 °C	/	PTFE -196 / +250 °C
	KALREZ -20 / +250 °C	/	KALREZ -20 / +275 °C
Connessione Entrata Inlet Connection	G.3/8" - 1/2" ISO228	/	G.3/8" - 1/2" ISO228
	R.3/8" - 1/2" EN10226	/	R.3/8" - 1/2" EN10226
	3/8" - 1/2" NPT	/	3/8" - 1/2" NPT
	/	/	3/4" Tri Clamp
	/	/	/
	/	/	/
Connessione Uscita Outlet Connection	/	/	/
	/	/	/
	/	/	/
	/	/	/
	/	/	/
	/	/	/

A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: INAIL (area ISPESL), TÜV, RINA, Bureau Veritas, ABS e Lloyd Register.
On request tests can be made by the most prestigious societies, such as: INAIL (area ISPESL), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.

Note: