



Tipo : Type :		F18		do: 18 mm	
Omologazione Homologation		PN	Coefficiente efflusso ridotto Low flow coefficient	Campo di taratura Setting range	
CE - UKCA		40	0,74; >3 bar 0,84	0,3 - 21,0 bar	
EAC		40	0,74; >3 bar 0,84	0,3 - 21,0 bar	
ATEX Ex h II 2 Gb - UKEX (1)		40	0,74; >3 bar 0,84	0,3 - 21,0 bar	
ATEX Ex h II 2 Db - UKEX		/	/	/	
ASME XIII - CRN (Canada)		40	0,712	1,0 - 21,0 bar	
SELO - TSG		40	0,712	1,0 - 21,0 bar	
CONFIGURAZIONE - CONFIGURATION					
Materiale Material		Ottone Brass	Mista Ottone-Acciaio inox Mixed Brass-Stainles steel	Acciaio inox Stainles steel	
Modelli Model	Con ghiera With ring nut	/	/	/	
	Senza Ghiera Without ring nut	/	/	/	
	Con protezione With Protection	/	/	/	
	/	/	/	/	
	/	/	/	/	
	/	/	/	/	
Sedi di Tenuta Seal System	N.B.R. (Std) -10 / + 100 °C	/	/	/	
	E.P.D.M. -50 / + 150 °C	/	/	/	
	VITON -20 / +200 °C	/	/	/	
	SILICONE -60 / +200 °C	/	/	/	
	PTFE -196 / +250 °C	/	/	/	
	KALREZ -20 / +250 °C	/	/	/	
Connessione Entrata Inlet Connection	G.1" ISO228	/	/	/	
	R.1" EN10226	/	/	/	
	1" NPT	/	/	/	
	/	/	/	/	
	/	/	/	/	
	/	/	/	/	
	/	/	/	/	
	/	/	/	/	
Connessione Uscita Outlet Connection	/	/	/	/	
	/	/	/	/	
	/	/	/	/	
	/	/	/	/	
	/	/	/	/	
	/	/	/	/	
A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: INAIL (area ISPEL), TÜV, RINA, Bureau Veritas, ABS e Lloyd Register On request tests can be made by the most prestigious societies, such as: INAIL (area ISPELS), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.					

A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: INAIL (area ISPESL), TÜV, RINA, Bureau Veritas, ABS e Lloyd Register.
On request tests can be made by the most prestigious societies, such as: INAIL (area ISPESL), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.

Note: (1) No Modello Con protezione / No Model With P