



Tipo : Type :		G20		24
		do:	20 mm	
Omologazione Homologation	PN	Coefficiente efflusso ridotto Low flow coefficient	Campo di taratura Setting range	
CE - UKCA	60	0,83	0,3 - 60,0 bar	
EAC	60	0,83	0,3 - 60,0 bar	
ATEX Ex h II 2 Gb - UKEX	60	0,83	0,3 - 60,0 bar	
ATEX Ex h II 2 Db - UKEX (1)	60	0,83	0,3 - 60,0 bar	
ASME XIII - CRN (Canada)	60	0,629	1,0 - 60,0 bar	
SELO - TSG	60	0,629	1,0 - 60,0 bar	
CONFIGURAZIONE - CONFIGURATION				
Materiale Material	Ottone Brass	Mista Ottone-Acciaio inox Mixed Brass-Stainless steel	Acciaio inox Stainless steel	
Modelli Model	Con ghiera With ring nut	Con ghiera With ring nut	Con ghiera With ring nut	
	Senza Ghiera Without ring nut	Senza Ghiera Without ring nut	Senza Ghiera Without ring nut	
	Con leva With lever	Con leva With lever	Con leva With lever	
	/	/	Con apertura pneumatica (2) Nith pneumatic opening	
	/	/	Pneumatica con sensore (2) Pneumatic with sensor	
Sedi di Tenuta Seal System	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICONE -60 / +200 °C PTFE -196 / +250 °C KALREZ -20 / +250 °C /	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICONE -60 / +200 °C PTFE -196 / +250 °C KALREZ -20 / +250 °C Metal -196 / +250 °C	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICONE -60 / +200 °C PTFE -196 / +250 °C KALREZ -20 / +275 °C Metal -196 / +450 °C	
Connessione Entrata Inlet Connection	G.1" - 1"1/4 ISO228 G.1" - 1"1/4 ISO228 F. R.1" - 1"1/4 EN10226 1" - 1"1/4 NPT / / / / /	G.1" - 1"1/4 ISO228 G.1" - 1"1/4 ISO228 F. R.1" - 1"1/4 EN10226 1" - 1"1/4 NPT 1" - 1"1/2 Tri Clamp DN25-32-40 DIN405-11851 DN20-25-32 PN16-40 1" - 1"1/2 150-300 lb /	G.1" - 1"1/4 ISO228 G.1" - 1"1/4 ISO228 F. R.1" - 1"1/4 EN10226 1" - 1"1/4 NPT 1" - 1"1/2 Tri Clamp DN25 32-40 DIN405-11851 DN20-25-32 PN16-40 1" - 1"1/2 150-300 lb /	
Connessione Uscita Outlet Connection	G.1"1/4 ISO228 / / / / /	G.1"1/4 ISO228 1"1/2 Tri Clamp DN25-32-40 DIN405-11851 DN32-40 PN16-40 1"1/4-1"1/2-2" 150-300 lb / /	G.1"1/4 ISO228 1"1/2 Tri Clamp DN25-32-40 DIN405-11851 DN32-40 PN16-40 1"1/4-1"1/2-2" 150-300 lb / /	
A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: INAIL (area ISPESL), TÜV, RINA, Bureau Veritas, ABS e Lloyd Register. On request tests can be made by the most prestigious societies, such as: INAIL (area ISPESL), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.				

Note: (1) No Modello Con leva / No Model With lever (2) Max 8 bar