



Tipo : Type :		G25		do: 25 mm	
Omologazione Homologation		PN	Coefficiente efflusso ridotto Low flow coefficient	Campo di taratura Setting range	
CE - UKCA		60	0,78	0,3 - 60,0 bar	
EAC		60	0,78	0,3 - 60,0 bar	
ATEX Ex h II 2 Gb - UKEX		60	0,78	0,3 - 60,0 bar	
ATEX Ex h II 2 Db - UKEX (1)		60	0,78	0,3 - 60,0 bar	
ASME XIII - CRN (Canada)		60	0,629	1,0 - 60,0 bar	
SELO - TSG		60	0,629	1,0 - 60,0 bar	
CONFIGURAZIONE - CONFIGURATION					
Materiale Material	Ottone Brass	Mista Ottone-Acciaio inox Mixed Brass-Stainless steel	Acciaio inox Stainless steel		
Modelli Model	Con ghiera With ring nut	Con ghiera With ring nut	Con ghiera With ring nut		
	Senza Ghiera Without ring nut	Senza Ghiera Without ring nut	Senza Ghiera Without ring nut		
	Con leva With lever	Con leva With lever	Con leva With lever		
	/	/	Con apertura pneumatica (2) Nith pneumatic opening		
	/	/	Pneumatica con sensore (2) Pneumatic with sensor		
Sedi di Tenuta Seal System	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICONE -60 / +200 °C PTFE -196 / +250 °C KALREZ -20 / +250 °C /	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICONE -60 / +200 °C PTFE -196 / +250 °C KALREZ -20 / +250 °C Metal -196 / +250 °C	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICONE -60 / +200 °C PTFE -196 / +250 °C KALREZ -20 / +275 °C Metal -196 / +450 °C		
	G.1"1/4 - 1"1/2 ISO228 G.1"1/2 ISO228 F. R.1"1/4 - 1"1/2 EN10226 1"1/4 - 1"1/2 NPT / / / / /	G.1"1/4 - 1"1/2 ISO228 G.1"1/2 ISO228 F. R.1"1/4 - 1"1/2 EN10226 1"1/4 - 1"1/2 NPT 1"1/2 Tri Clamp DN25-32-40 DIN405-11851 DN25-32-40 PN16-40 1"1/4 - 1"1/2 150-300 lb / /	G.1"1/4 - 1"1/2 ISO228 G.1"1/2 ISO228 F. R.1"1/4 - 1"1/2 EN10226 1"1/4 - 1"1/2 NPT 1"1/2 Tri Clamp DN25-32-40 DIN405-11851 DN25-32-40 PN16-40 1"1/4 - 1"1/2 150-300 lb / /		
Connessione Entrata Inlet Connection					
Connessione Uscita Outlet Connection	G.1"1/2 ISO228 / / / / / /	G.1"1/2 ISO228 1"1/2 Tri Clamp DN32-40 DIN405-11851 DN40-50 PN16-40 1"1/2 - 2" 150-300 lb / /	G.1"1/2 ISO228 1"1/2 Tri Clamp DN32-40 DIN405-11851 DN40-50 PN16-40 1"1/2 - 2" 150-300 lb / /		
A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: INAIL (area ISPESL), TÜV, RINA, Bureau Veritas, ABS e Lloyd Register. On request tests can be made by the most prestigious societies, such as: INAIL (area ISPESL), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.					

Note: (1) No Modello Con leva / No Model With lever (2) Max 8 bar